

Features

- N-Channel
40V/7.8A,
 $R_{DS(ON)} = 11m\Omega$ (Typ.) @ $V_{GS}=10V$
- P-Channel
-40V/-6.4A,
 $R_{DS(ON)} = 26m\Omega$ (Typ.) @ $V_{GS}=-10V$
- Very low on-resistance
- Fast Switching


Applications

- Load Switch



Halogen-Free

Pin Description



Absolute Maximum Ratings

Symbol	Parameter	N-Channel	P-Channel	Unit
Common Ratings ($T_A=25^\circ C$ Unless Otherwise Noted)				
V_{DSS}	Drain-Source Voltage	40	-40	V
V_{GSS}	Gate-Source Voltage	± 20	± 20	
T_J	Maximum Junction Temperature	150	150	$^\circ C$
T_{STG}	Storage Temperature Range	-55 to 150	-55 to 150	$^\circ C$
I_S	Diode Continuous Forward Current	$T_A=25^\circ C$	1.6	-1.6
Mounted on Large Heat Sink				
$I_{DP}^{(1)}$	300 μ s Pulse Drain Current Tested	$T_A=25^\circ C$	31	-25
$I_D^{(2)}$	Continuous Drain Current($V_{GS}=\pm 10V$)	$T_A=25^\circ C$	7.8	-6.4
		$T_A=70^\circ C$	6.2	-5.1
P_D	Maximum Power Dissipation	$T_A=25^\circ C$	2	2
		$T_A=70^\circ C$	1.3	1.3
$R_{\theta JL}$	Thermal Resistance-Junction to Lead	24	24	$^\circ C/W$
$R_{\theta JA}^{(3)}$	Thermal Resistance-Junction to Ambient	62.5	62.5	$^\circ C/W$
Drain-Source Avalanche Ratings				
$E_{AS}^{(4)}$	Avalanche Energy, Single Pulsed	25	36	mJ

Electrical Characteristics ($T_A=25^\circ\text{C}$ Unless Otherwise Noted)

Symbol	Parameter	Test Condition	KS4618HB			Unit	
			Min.	Typ.	Max.		
Static Characteristics							
BV_{DSS}	Drain-Source Breakdown Voltage	$V_{\text{GS}}=0\text{V}, I_{\text{DS}}=250\mu\text{A}$	N	40		V	
		$V_{\text{GS}}=0\text{V}, I_{\text{DS}}=-250\mu\text{A}$	P	-40			
I_{DSS}	Zero Gate Voltage Drain Current	$V_{\text{DS}}=40\text{V}, V_{\text{GS}}=0\text{V}$	N		1	μA	
		$T_J=125^\circ\text{C}$			30		
		$V_{\text{DS}}=-40\text{V}, V_{\text{GS}}=0\text{V}$	P		-1		
		$T_J=125^\circ\text{C}$			-30		
$V_{\text{GS}(\text{th})}$	Gate Threshold Voltage	$V_{\text{DS}}=V_{\text{GS}}, I_{\text{DS}}=250\mu\text{A}$	N	1.1	1.6	V	
		$V_{\text{DS}}=V_{\text{GS}}, I_{\text{DS}}=-250\mu\text{A}$	P	-1.1	-1.6		
I_{GSS}	Gate Leakage Current	$V_{\text{GS}}=\pm 20\text{V}, V_{\text{DS}}=0\text{V}$	N		± 100	nA	
		$V_{\text{GS}}=\pm 20\text{V}, V_{\text{DS}}=0\text{V}$	P		± 100		
$R_{\text{DS}(\text{ON})}^{(5)}$	Drain-Source On-state Resistance	$V_{\text{GS}}=10\text{V}, I_{\text{DS}}=8\text{A}$	N		11	$\text{m}\Omega$	
		$V_{\text{GS}}=-10\text{V}, I_{\text{DS}}=-7\text{A}$	P		26		
		$V_{\text{GS}}=4.5\text{V}, I_{\text{DS}}=6\text{A}$	N		17		
		$V_{\text{GS}}=-4.5\text{V}, I_{\text{DS}}=-5\text{A}$	P		39		
Diode Characteristics							
$V_{\text{SD}}^{(5)}$	Diode Forward Voltage	$I_{\text{SD}}=7\text{A}, V_{\text{GS}}=0\text{V}$	N		0.86	V	
		$I_{\text{SD}}=-7\text{A}, V_{\text{GS}}=0\text{V}$	P		-0.86		
t_{rr}	Reverse Recovery Time	N-Channel $I_{\text{SD}}=7\text{A}, dI_{\text{SD}}/dt=100\text{A}/\mu\text{s}$	N		8	ns	
			P		16		
Q_{rr}	Reverse Recovery Charge		N		7	nC	
			P		6		
Dynamic Characteristics ⁽⁶⁾							
R_{G}	Gate Resistance	$V_{\text{GS}}=0\text{V}, V_{\text{DS}}=0\text{V}, F=1\text{MHz}$	N		3.3	Ω	
			P		9.5		
C_{iss}	Input Capacitance	N-Channel $V_{\text{GS}}=0\text{V}, V_{\text{DS}}=20\text{V},$ Frequency=1.0MHz	N		1290	pF	
			P		1310		
C_{oss}	Output Capacitance		N		100		
			P		115		
C_{rss}	Reverse Transfer Capacitance	P-Channel $V_{\text{GS}}=0\text{V}, V_{\text{DS}}=-20\text{V},$ Frequency=1.0MHz	N		85	pF	
			P		90		

Electrical Characteristics ($T_A=25^\circ\text{C}$ Unless Otherwise Noted)


Symbol	Parameter	Test Condition	KS4618HB			Unit	
			Min.	Typ.	Max.		
Dynamic Characteristics⁽⁶⁾							
$t_{d(\text{ON})}$	Turn-on Delay Time	N-Channel $V_{DD}=20\text{V}$, $I_{DS}=7\text{A}$, $V_{GEN}=10\text{V}$, $R_G=3\Omega$	N	7		ns	
			P	8			
	Turn-on Rise Time		N	4			
			P	6			
	Turn-off Delay Time	P-Channel $V_{DD}=-20\text{V}$, $I_{DS}=-7\text{A}$, $V_{GEN}=-10\text{V}$, $R_G=3\Omega$	N	21			
			P	35			
	Turn-off Fall Time		N	5			
			P	10			
Gate Charge Characteristics⁽⁶⁾							
Q_g	Total Gate Charge	N-Channel $V_{DS}=20\text{V}$, $V_{GS}=10\text{V}$, $I_{DS}=7\text{A}$	N	16		nC	
			P	23			
	Gate-Source Charge	P-Channel $V_{DS}=-20\text{V}$, $V_{GS}=-10\text{V}$, $I_{DS}=-7\text{A}$	N	3.1			
			P	3.9			
Q_{gd}	Gate-Drain Charge		N	4			
			P	5.4			

Notes:

- ①Pulse width limited by safe operating area.
- ②Calculated continuous current based on maximum allowable junction temperature.
- ③When mounted on 1 inch square copper board, $t \leq 10\text{sec}$. The value in any given application depends on the user's specific board design.
- ④Limited by $T_{J\max}$. Starting $T_J = 25^\circ\text{C}$, N Channel: $L = 0.5\text{mH}$, $R_G = 25\Omega$, $I_{AS} = 10\text{A}$, $V_{GS} = 10\text{V}$, P-Channel: $L = 0.5\text{mH}$, $R_G = 25\Omega$, $I_{AS} = -12\text{A}$, $V_{GS} = -10\text{V}$, Part not recommended for use above this value.
- ⑤Pulse test; Pulse width $\leq 300\mu\text{s}$, duty cycle $\leq 2\%$.
- ⑥Guaranteed by design, not subject to production testing.

Ordering and Marking Information

Device	Package	Packaging	Quantity	Reel Size	Tape width
KS4618HB	SOP8	Tape&Reel	3000	13"	12mm








Y =Year,2017-A,2018-B,etc.







WW =Week.

XXX =Lot number.






Typical Characteristics(N-Channel)









Typical Characteristics(N-Channel)




Typical Characteristics(P-Channel)




Typical Characteristics(P-Channel)




Package Information
SOP8


SYMBOL	MM			INCH		
	MIN	NOM	MAX	MIN	NOM	MAX
A	1.300	1.525	1.750	0.051	0.060	0.069
A1	0.050	0.150	0.250	0.002	0.006	0.010
A2	1.350	1.450	1.550	0.053	0.057	0.061
b	0.330	0.420	0.510	0.013	0.017	0.020
c	0.170	0.210	0.250	0.007	0.008	0.010
D	4.700	4.900	5.100	0.185	0.193	0.201
E	3.800	3.900	4.000	0.150	0.154	0.157
E1	5.800	6.000	6.200	0.228	0.236	0.244
e	1.270 BSC			0.050 BSC		
L	0.400	0.835	1.270	0.016	0.033	0.050
θ	0°		8°	0°		8°


Avalanche Test Circuit and Waveforms(N-Channel)




Switching Time Test Circuit and Waveforms(N-Channel)




Diode Recovery Test Circuit and Waveforms(N-Channel)




Gate Charge Test Circuit and Waveform(N-Channel)




Avalanche Test Circuit and Waveforms(P-Channel)




Switching Time Test Circuit and Waveforms(P-Channel)



Diode Recovery Test Circuit and Waveforms(P-Channel)



Gate Charge Test Circuit and Waveform(P-Channel)



Customer Service

Kwansemi Semiconductor Co.,Ltd

Email:Sales@kwansemi.com

Web:www.kwansemi.com

DISCLAIMER:

Kwansemi reserves the right to change the specifications and circuitry without notice at any time. The Products are not designed for use in hostile environments, including, without limitation, aircraft, nuclear power generation, medical appliances, and devices or systems in which malfunction of any Product can reasonably be expected to result in a personal injury. Seller's customers using or selling Seller's products for use in such applications do so at their own risk and agree to fully defend and indemnify Seller.